

# Xerox® WorkCentre® 7525/7530/7535/7545/7556

## Multifunction Printer



WorkCentre 7500 series shown with 1 Tray Option and Work Surface



WorkCentre 7500 series shown with 3 Tray Option



WorkCentre 7500 series shown with High Capacity Tandem Tray Option, Work Surface and Integrated Office Finisher (optional only with 7525/7530/7535)



WorkCentre 7500 series shown with High Capacity Tandem Tray Option, Work Surface and Office Finisher LX with Booklet Maker Option



WorkCentre 7500 series shown with High Capacity Tandem Tray Option, Work Surface and Professional Finisher

| System Specifications               |   |                 |                 |                 |                 |
|-------------------------------------|---|-----------------|-----------------|-----------------|-----------------|
| Output Speed (Printing and Copying) | WorkCentre 7525   | WorkCentre 7530 | WorkCentre 7535 | WorkCentre 7545 | WorkCentre 7556 |
| Color                               | Up to 25 ppm  | Up to 30 ppm    | Up to 35 ppm    | Up to 45 ppm    | Up to 50 ppm    |
| Black and White                     | Up to 25 ppm  | Up to 30 ppm    | Up to 35 ppm    | Up to 45 ppm    | Up to 55 ppm    |
| Functions                           |   |                 |                 |                 |                 |
| <b>Standard</b>                     | Copy, Print (Adobe® PostScript® 3™, PCL, XML Paper Specifications (XPS), PDF, Print from USB) Scan Kit (Scan to USB, Email, Mailbox, Network Folder, Home), Fax (Server Fax integration, Internet Fax), Data Security (Hard Disk encryption, Disk Overwrite), Network Accounting, EIP |                 |                 |                 |                 |
| <b>Optional</b>                     | Walk-up Fax (One- or Two-line), ScanFlowStore®, SMARTsend®, CAC / Personal Identification Verification (PIV), Xerox Secure Access Unified ID System®<br>EFI® Fiery Workflow   |                 |                 |                 |                 |
| Specifications                      |   |                 |                 |                 |                 |
| <b>Processor</b>                    | 1.5 GHz   |                 |                 |                 |                 |
| <b>Memory</b>                       | 2 GB system plus 1 GB page memory   |                 |                 |                 |                 |
| <b>Hard Drive</b>                   | 160 GB  |                 |                 |                 |                 |
| <b>Connectivity</b>                 | 10/100/1000Base-T Ethernet<br>High-Speed USB 2.0<br>Wireless Ethernet 802.11b (via third-party adapters)  |                 |                 |                 |                 |
| <b>USB Port</b>                     | PC Interface for Xerox® Copier Assistant® via USB Type B port<br>Software upgrade via USB Type A port<br>USB Print and Scan   |                 |                 |                 |                 |

|  |  |                         |                         |                        |                        |
|--|--|-------------------------|-------------------------|------------------------|------------------------|
| <b>Control Panel Languages</b>   | Languages: (Select from 18 languages for user interface – International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian or Romanian)  |                         |                         |                        |                        |
| <b>Copy</b>  |  |                         |                         |                        |                        |
| <b>First-Copy-Out Time</b><br>(Letter-size/A4, from Platen to Center Tray) | <b>WorkCentre 7525</b>   | <b>WorkCentre 7530</b>  | <b>WorkCentre 7535</b>  | <b>WorkCentre 7545</b> | <b>WorkCentre 7556</b> |
| <b>Color</b>   | As fast as 13.2 seconds  | As fast as 10.9 seconds | As fast as 11.0 seconds | As fast as 7.8 seconds | As fast as 7.2 seconds |
| <b>Black and White</b>   | As fast as 11.1 seconds  | As fast as 8.7 seconds  | As fast as 8.6 seconds  | As fast as 6.6 seconds | As fast as 5.8 seconds |
| <b>Copy Specifications</b>   |  |                         |                         |                        |                        |
| <b>Sides (input:output)</b>  | 1-1, 1-2, 2-2, 2-1   |                         |                         |                        |                        |
| <b>Quantity</b>  | 1 to 9,999   |                         |                         |                        |                        |
| <b>Resolution (max)</b>  | Scan at 600 x 600 dpi, output at 1200 x 2400 dpi   |                         |                         |                        |                        |
| <b>Reduction/Enlargement</b>   | Variable Zoom from 25% - 400% in 1% increments   |                         |                         |                        |                        |
| <b>Concurrency</b>   | Program-ahead to allow job to be initiated while initial job is processed (Copy, Print, Fax and Scan)  |                         |                         |                        |                        |
| <b>Basic Copy Features &amp; Options</b>                                   | Collation<br>Automatic 2-sided/Duplex<br>Auto Reduction & Enlargement to fit selected paper size<br>Hole Punching<br>Booklet Creation<br>Stapling<br>Large Job Interrupt<br>Auto Paper Select<br>Authentication for Services (i.e. Color Copy)<br>Auto Tray Switching<br>Features Help (Intuitive text and graphic descriptions)   |                         |                         |                        |                        |
| <b>Imaging Copy Features</b>   | Image Quality: <ul style="list-style-type: none"> <li>• Original Type Selection: Photo &amp; Text, Photo, Text, Newspaper/Magazine, Inkjet Original, Maps.</li> <li>• Image Options: Lighten/Darken, Sharpness, Saturation.</li> <li>• Image Enhancement: Auto Background Suppression, Auto and Manual Contrast.</li> <li>• Color Effects: Off, Single Color, Lively, Bright, Warm, Cool.</li> <li>• Color Balance: Normal, Basic Color Balance, Advanced Color Balance</li> </ul> Book Copying/Bound Copying<br>Edge Erase<br>Single Color<br>Repeat Image<br>Mixed Size Original<br>Image Shift (with Auto Center option)<br>Image Shift Preset: Support for 3 Preset Options<br>Annotation and Bates™ stamping (with color capability and font size adjustment) |                         |                         |                        |                        |
| <b>Output Copy Features</b>  | Covers (Front only, front and back, back only, printed inside and out: Blank or Printed)<br>Build Job: (Enables page-level programming and also lets you proof each section or delete last section as the job is built)<br>Transparencies<br>Dividers (blank)<br>Multi-up (up to 15 columns by 15 rows)<br>Invert Image (negative or mirror image)<br>Sample Set<br>Job Settings<br>Save Job Settings  |                         |                         |                        |                        |

| Paper Handling                                    |  |
|---|--|
| <b>Duplex Automatic Document Feeder</b>           |  |
| <b>Capacity<sup>1</sup></b>                       | 110 sheets   |
| <b>Speed</b>                                      | up to 70 images per minute mono and color  |
| <b>Paper Sizes Sensed</b>                         | 5.5 x 8.5 in. to 11 x 17 in. / A5 to A3  |
| <b>Weights</b>                                    | 16 lb bond to 32 lb bond (50 gsm to 128 gsm)   |
| <b>Bypass Tray</b>                                |  |
| <b>Capacity<sup>1</sup></b>                       | 100 sheets   |
| <b>Sizes</b>                                      | Custom sizes up to 12.6 x 19 in. / 320 x 483 mm  |
| <b>Weights</b>                                    | 16 lb bond to 110 lb cover (55 to 300 gsm)   |
| <b>Types</b>                                      | Plain<br>Bond<br>Lightweight<br>Heavyweight<br>Extra Heavyweight<br>Extra Heavyweight Plus<br>Gloss<br>Heavyweight Gloss<br>Extra Heavyweight Gloss<br>Labels<br>Transparencies<br>Custom<br>Envelopes |
| <b>1 Tray Option (Includes Tray 1 and Tray 2)</b> |  |
| <b>Capacity<sup>1</sup></b>                       | Tray 1: 520 sheets<br>Tray 2: 520 sheets   |
| <b>Sizes</b>                                      | Tray 1: Custom Sizes from 5.5 x 7.5 in. SEF to 11.7 x 17 in. SEF / 140 x 182 mm to 297 x 432 mm<br>Tray 2: Custom Sizes from 5.5 x 7.5 in. SEF to 12.6 x 18 in. SEF / 140 x 182 mm to 320 x 457 mm     |
| <b>Weights</b>                                    | 16 lb bond to 140 lb index (60 to 256 gsm)   |
| <b>Types</b>                                      | Plain<br>Bond<br>Heavyweight<br>Extra Heavyweight<br>Gloss<br>Heavyweight Gloss<br>Labels<br>Transparencies<br>Custom  |
| <b>3 Tray Option (Includes Trays 1-4)</b>         |  |
| <b>Capacity<sup>1</sup></b>                       | Trays 1-4: 520 sheets each tray  |
| <b>Sizes</b>                                      | Tray 1: Custom Sizes from 5.5 x 7.5 in. SEF to 11.7 x 17 in. SEF / 140 x 182 mm to 297 x 432 mm<br>Trays 2-4: Custom Sizes from 5.5 x 7.5 in. SEF to 12.6 x 18 in. SEF / 140 x 182 mm to 320 x 457 mm  |
| <b>Weights</b>                                    | 16 lb bond to 140 lb index (60 to 256 gsm)   |

<sup>1</sup> Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

|   |   |
|---|---|
| <b>Types</b>  | Plain<br>Bond<br>Heavyweight<br>Extra Heavyweight<br>Gloss<br>Heavyweight Gloss<br>Labels<br>Transparencies<br>Custom   |
| <b>High Capacity Tandem Tray Option</b>   |   |
| <b>Capacity<sup>1</sup></b>   | Tray 1: 520 sheets<br>Tray 2: 520 sheets<br>Tray 3: 867 sheets<br>Tray 4: 1,133 sheets  |
| <b>Sizes</b>  | Tray 1: Custom Sizes from 5.5 x 7.5 in. SEF to 11.7 x 17 in. SEF / 140 x 182 mm to 297 x 432 mm<br>Tray 2: Custom Sizes from 5.5 x 7.5 in. SEF to 12.6 x 18 in. SEF / 140 x 182 mm to 320 x 457 mm<br>Trays 3-4: Standard Sizes: 7.25 x 10.5 in., 8.5 x 11 in. LEF / A4 |
| <b>Weights</b>  | 16 lb bond to 140 lb index (60 to 256 gsm)  |
| <b>Types</b>  | Plain<br>Bond<br>Heavyweight<br>Extra Heavyweight<br>Gloss<br>Heavyweight Gloss<br>Labels<br>Transparencies<br>Custom   |
| <b>High Capacity Feeder (HCF) (Optional with 3 Tray Option or High Capacity Tandem Tray Option)</b> |   |
| <b>Capacity<sup>1</sup></b>   | 2000 sheets   |
| <b>Sizes</b>  | Standard Sizes: 7.25 x 10.5 in., 8.5 x 11 in. LEF / A4  |
| <b>Weights</b>  | 16 lb bond to 140 lb index (55 to 256 gsm)  |
| <b>Envelope Tray (Optional - Replaces Tray 1)</b>   |   |
| <b>Capacity<sup>1</sup></b>   | Up to 60 envelopes  |
| <b>Sizes</b>  | #10 Commercial (9.25 x 4.125 in.), Monarch, DL, C5<br>Custom sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in. (98 x 148 mm to 162 x 241 mm)  |
| <b>Weights</b>  | 20 lb bond to 24 lb bond (75 to 90 gsm)   |
| <b>Total Capacity</b>   |   |
| <b>Device Total Capacity</b>  | 5,140 sheets  |
| <b>Paper Output / Finishing</b>   |   |
| <b>Output Trays (Standard)</b>  |   |
| <b>Stacking Trays<sup>1</sup></b>   | Dual Offset Catch Tray – up to 250 sheets each<br>Left-side Face up Tray – up to 100 sheets   |

<sup>1</sup> Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

| Output – Integrated Office Finisher (Optional with 7525/7530/7535)                   |  |  |
|--|--|--|
| Stacking Tray  | 500 sheets of 20 lb bond (80 gsm) 8.5 x 11 in./A4 or 250 sheets of 20 lb bond (80 gsm) 11 x 17 in./A3  |  |
| Sizes  | 3.5 x 3.9 in. to 11 x 17 in. / 89 x 98 mm to A3  |  |
| Weights  | 16 lb bond to 80 lb cover / 60 to 220 gsm  |  |
| Stapling   | Single<br>Auto stapling:<br>50 sheets maximum: Letter/A4/B5-size sheets (less than 90 gsm or (2) 220 gsm covers)<br>30 sheets maximum: Legal/Tabloid/A3/B4-size sheets (less than 90 gsm or (2) 220 gsm covers)                              |  |
| Office Finisher LX (Optional)  |  |  |
| Capacity <sup>1</sup>  | Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in./A4)  |  |
| Sizes  | 7.2 x 8.3 in. to 11 x 17 in. / 182 x 210 mm to A3  |  |
| Weights  | 16 lb bond to 80 lb cover (60 to 220 gsm)  |  |
| Multiposition Stapling   | 50 sheets of 24 lb bond (90 gsm)   |  |
| Hole Punch (Optional)  | <b>North America</b><br>2-3 Hole Punch   | <b>Europe</b><br>2-4 Hole Punch                                    |
| Booklet Maker for Office Finisher LX (Score/Crease, Saddle-stitch Staple) (Optional) |  |  |
| Capacity   | 40 booklets (2-15 sheets per booklet – 20 lb/80 gsm or less)   |  |
| Sizes  | Letter – 8.5 x 11 in. (A4) SEF<br>Legal – 8.5 x 14 in. (216 x 356 mm) SEF<br>Ledger – 11 x 17 in. (A3) SEF   |  |
| Saddle-stitch Stapling   | 2-15 sheets / 8 – 60 page booklet<br>16 lb bond to 24 lb bond / 60 to 90 gsm   |  |
| Score/Crease   | 1-15 sheets / unstapled  |  |
| Professional Finisher (Optional)   |  |  |
| Capacity <sup>1</sup>  | Top Tray: 500 sheets of 8.5 x 11 in. / A4 unstapled<br>Stacking Stapling Tray: 1,500 sheets of 8.5 x 11 in. / 11 x 17 in. / A4 / A3 / SRA3 unstapled or 200 stapled sets of 8.5 x 11 in. / A4 or 100 stapled sets of 11 x 17 in. / A3 / SRA3 |  |
| Sizes  | 8 x 10 in. to 12 x 18 in. / B5 to SRA3   |  |
| Weights  | 16 lb bond to 80 lb cover (60 to 220 gsm)  |  |
| Stapling   | Single and multiposition stapling<br>Auto stapling (50 sheets maximum) – 24 lb/90 gsm<br>Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported   |  |
| Hole Punch (Standard)  | <b>North America</b><br>2-3 Hole Punch   | <b>Europe</b><br>2-4 Hole Punch<br>4 Hole Swedish Punch (Optional) |
| Booklet Maker  | Saddle-stitch 2 to 15 sheets of 24 lb / 90 gsm or less<br>V-fold up to 5 sheets<br>Letter, Legal, Tabloid, A3, A4, SRA3 supported  |  |
| Convenience Stapler (Optional - Includes Work Surface)                               |  |  |
| Capacity <sup>1</sup>  | 50-sheet stapling<br>5,000 staples<br>Requires a separate outlet   |  |

<sup>1</sup> Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

| Print   |   |   |   |
|---|---|---|---|
| Print Controller  |   |   |   |
| <b>Page Description Languages (PDL) (Standard)</b>  | PCL® 6<br>PCL® 5c<br>Adobe® PostScript® 3™<br>PDF<br>XPS®<br>HP-GL2™<br>TIFF  |   |   |
| <b>Print resolution</b>   | Print Engine: up to 1200 x 2400 dpi <ul style="list-style-type: none"> <li>• Toner Saver - 600x600 dots per inch, with limits on maximum saturation</li> <li>• Standard - 600x600 dots per inch with 256 halftone levels.</li> <li>• Enhanced - Raster image processing at 600x600 dots per inch with eight bits per pixel. Halftone creation with resolution enhancement and LED marking at 1200x2400 dots per inch with 256 halftone levels.</li> <li>• High Resolution - 1200x1200 dots per inch with 256 halftone levels.</li> </ul>  |   |   |
| <b>Print Features</b>   | <table border="0" style="width: 100%;"> <tr> <td style="vertical-align: top; width: 50%;">                             Application defaults<br/>                             Banner Sheet enable/disable<br/>                             Bi-directional status<br/>                             Color Options                             <ul style="list-style-type: none"> <li>• Automatic Color</li> <li>• Vivid Color</li> <li>• Black and White</li> <li>• Custom Color Options                                     <ul style="list-style-type: none"> <li>- Color By Words</li> <li>- Color Correction (allows for different RGB, CMYK, Spot and other specifications)</li> <li>- Color Adjustments (Lightness, Contrast, Saturation, Color cast)</li> </ul> </li> </ul>                             Cover selection<br/>                             Delay Print (specific time)<br/>                             Duplex (2-sided)<br/>                             Enhanced Gloss at normal speed<br/>                             User Permissions required to access Print and Print Features (e.g. color access, or time restrictions) reflects in the print driver<br/>                             Finishing                             <ul style="list-style-type: none"> <li>• Multiple stapling positions</li> <li>• Hole punch</li> <li>• Booklet creation</li> <li>• Fit to new paper size</li> <li>• Saddle stitch with Professional finisher</li> <li>• Output tray selections</li> <li>• Store and recall driver setting Inserts and exception pages</li> </ul>                             Image Options                             <ul style="list-style-type: none"> <li>• Toner Saver</li> <li>• Resolution options (Standard, High resolution, Enhanced, Toner Saver)</li> <li>• Reduction/Enlargement</li> <li>• Rotate 180 degrees</li> <li>• Margins</li> <li>• Mirrored output</li> </ul> </td> <td style="vertical-align: top; width: 50%;">                             Job identification (Print ID or Banner, Print ID in margins on first page only or all pages)<br/>                             Job Type                             <ul style="list-style-type: none"> <li>• Secure, Sample, Delay, Save</li> </ul>                             Layout/Watermark (N-up (16) / Multi-up, Booklet Layout / Finishing, Fit to new paper size)<br/>                             Margins<br/>                             Mirror image<br/>                             N-up<br/>                             Overlays<br/>                             Paper selection by attribute<br/>                             Print calibration<br/>                             Print to Fax (requires optional Fax kit)<br/>                             Sample Set<br/>                             Scaling<br/>                             Secure Print<br/>                             Special Pages (exception page programming (covers, inserts, exception pages)<br/>                             Store and Recall driver settings<br/>                             Store file in folder<br/>                             Sustainability features                             <ul style="list-style-type: none"> <li>• Xerox Earth Smart settings                                     <ul style="list-style-type: none"> <li>- Duplex</li> <li>- N-up</li> <li>- Turn-off banner and print ID on document</li> <li>- Smart Sample set</li> </ul> </li> <li>• Hold All Jobs</li> </ul>                             Transparency separators                         </td> </tr> </table> | Application defaults<br>Banner Sheet enable/disable<br>Bi-directional status<br>Color Options <ul style="list-style-type: none"> <li>• Automatic Color</li> <li>• Vivid Color</li> <li>• Black and White</li> <li>• Custom Color Options                                     <ul style="list-style-type: none"> <li>- Color By Words</li> <li>- Color Correction (allows for different RGB, CMYK, Spot and other specifications)</li> <li>- Color Adjustments (Lightness, Contrast, Saturation, Color cast)</li> </ul> </li> </ul> Cover selection<br>Delay Print (specific time)<br>Duplex (2-sided)<br>Enhanced Gloss at normal speed<br>User Permissions required to access Print and Print Features (e.g. color access, or time restrictions) reflects in the print driver<br>Finishing <ul style="list-style-type: none"> <li>• Multiple stapling positions</li> <li>• Hole punch</li> <li>• Booklet creation</li> <li>• Fit to new paper size</li> <li>• Saddle stitch with Professional finisher</li> <li>• Output tray selections</li> <li>• Store and recall driver setting Inserts and exception pages</li> </ul> Image Options <ul style="list-style-type: none"> <li>• Toner Saver</li> <li>• Resolution options (Standard, High resolution, Enhanced, Toner Saver)</li> <li>• Reduction/Enlargement</li> <li>• Rotate 180 degrees</li> <li>• Margins</li> <li>• Mirrored output</li> </ul> | Job identification (Print ID or Banner, Print ID in margins on first page only or all pages)<br>Job Type <ul style="list-style-type: none"> <li>• Secure, Sample, Delay, Save</li> </ul> Layout/Watermark (N-up (16) / Multi-up, Booklet Layout / Finishing, Fit to new paper size)<br>Margins<br>Mirror image<br>N-up<br>Overlays<br>Paper selection by attribute<br>Print calibration<br>Print to Fax (requires optional Fax kit)<br>Sample Set<br>Scaling<br>Secure Print<br>Special Pages (exception page programming (covers, inserts, exception pages)<br>Store and Recall driver settings<br>Store file in folder<br>Sustainability features <ul style="list-style-type: none"> <li>• Xerox Earth Smart settings                                     <ul style="list-style-type: none"> <li>- Duplex</li> <li>- N-up</li> <li>- Turn-off banner and print ID on document</li> <li>- Smart Sample set</li> </ul> </li> <li>• Hold All Jobs</li> </ul> Transparency separators |
| Application defaults<br>Banner Sheet enable/disable<br>Bi-directional status<br>Color Options <ul style="list-style-type: none"> <li>• Automatic Color</li> <li>• Vivid Color</li> <li>• Black and White</li> <li>• Custom Color Options                                     <ul style="list-style-type: none"> <li>- Color By Words</li> <li>- Color Correction (allows for different RGB, CMYK, Spot and other specifications)</li> <li>- Color Adjustments (Lightness, Contrast, Saturation, Color cast)</li> </ul> </li> </ul> Cover selection<br>Delay Print (specific time)<br>Duplex (2-sided)<br>Enhanced Gloss at normal speed<br>User Permissions required to access Print and Print Features (e.g. color access, or time restrictions) reflects in the print driver<br>Finishing <ul style="list-style-type: none"> <li>• Multiple stapling positions</li> <li>• Hole punch</li> <li>• Booklet creation</li> <li>• Fit to new paper size</li> <li>• Saddle stitch with Professional finisher</li> <li>• Output tray selections</li> <li>• Store and recall driver setting Inserts and exception pages</li> </ul> Image Options <ul style="list-style-type: none"> <li>• Toner Saver</li> <li>• Resolution options (Standard, High resolution, Enhanced, Toner Saver)</li> <li>• Reduction/Enlargement</li> <li>• Rotate 180 degrees</li> <li>• Margins</li> <li>• Mirrored output</li> </ul> | Job identification (Print ID or Banner, Print ID in margins on first page only or all pages)<br>Job Type <ul style="list-style-type: none"> <li>• Secure, Sample, Delay, Save</li> </ul> Layout/Watermark (N-up (16) / Multi-up, Booklet Layout / Finishing, Fit to new paper size)<br>Margins<br>Mirror image<br>N-up<br>Overlays<br>Paper selection by attribute<br>Print calibration<br>Print to Fax (requires optional Fax kit)<br>Sample Set<br>Scaling<br>Secure Print<br>Special Pages (exception page programming (covers, inserts, exception pages)<br>Store and Recall driver settings<br>Store file in folder<br>Sustainability features <ul style="list-style-type: none"> <li>• Xerox Earth Smart settings                                     <ul style="list-style-type: none"> <li>- Duplex</li> <li>- N-up</li> <li>- Turn-off banner and print ID on document</li> <li>- Smart Sample set</li> </ul> </li> <li>• Hold All Jobs</li> </ul> Transparency separators   |   |   |
| <b>Print from USB</b>   | Allows walk-up printing from Type A USB port on front panel<br>Supports direct printing from computer via Type B USB port   |   |   |

| Print Protocols and Networks                 |  |
|--|--|
| <b>Operating Systems</b>                     | Microsoft Windows XP (32- and 64-bit), Windows Server 2003 (32- and 64-bit), Server 2008 (32- and 64-bit), Windows Vista (32- and 64-bit), Windows 7 (32- and 64-bit)<br>Mac OS 10.4 (PPD only)<br>Mac OS 10.5-10.6 (PostScript only)<br>Solaris 9, 10<br>HP UX 11, 11i<br>AIX 5<br>Linux RedHat Fedora Core 1-7<br>Linux RedHat Enterprise Linux 4<br>SUSE 10.X   |
| <b>Network Protocols</b>                     | TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD<br>NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway)<br>AppleTalk®: EtherTalk®<br>Microsoft Windows Networking over IP<br>(Most protocols not in use can be disabled)<br>Bonjour IPv6<br>Secure FTP  |
| <b>Administrative Protocols</b>              | DHCP, BOOTP, SNMP, WINS, DDNS, SLP® v2, HTTP, RARP, DHCP Autonet, SSL, NTP   |
| <b>Fonts</b>                                 | PCL: 94 scalable fonts, line printer and bitmap font (including Cyrillic font support)<br>PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts  |
| <b>Xerox® Mobile Express Driver® (X-MED)</b> | Makes it easy for mobile users to find, use and manage Xerox and non-Xerox devices in every new location. Plug into a new network, and X-MED automatically discovers available printers and provides status and capability information. Save a list of “favorite” printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT. <ul style="list-style-type: none"> <li>• Printers are automatically discovered</li> <li>• Printer list can be managed based on location</li> <li>• Gives Bi-directional feedback device status, supplies, queue management</li> </ul>   |
| <b>Xerox® Global Print Driver® (X-GPD)</b>   | A truly universal print driver that lets IT administrators install, upgrade and manage Xerox and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management. <ul style="list-style-type: none"> <li>• Lets IT managers qualify, deploy and manage all print devices on the network using a single driver</li> <li>• Fast and easy installation of new devices improves IT efficiency</li> <li>• Truly universal print driver supports Xerox and non-Xerox printers, PCL and PostScript</li> <li>• Gives Bi-directional feedback device status, supplies, queue management</li> </ul> |
| Scan   |  |
| <b>Concurrency</b>                           | Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing concurrent jobs)   |
| <b>Input Speed</b>                           | Scan at up to 70 ipm color scanning, up to 70 ipm black-and-white – 8.5 x 11 in. / A4 LEF  |
| <b>Resolution</b>                            | 600 x 600 dpi<br>400 x 400 dpi<br>300 x 300 dpi<br>200 x 200 dpi<br>150 x 150 dpi<br>100 x 100 dpi<br>72 x 72 dpi<br>Bit Depth: 1-bit (black and white), 8-bit (grayscale), 24-bit (color)   |
| <b>Maximum Scan Area</b>                     | 11 x 17 in. / A3   |
| <b>Scan Template Management</b>              | Support 250 scan templates<br>Create device specific CentreWare scan templates<br>Select confirmation sheet options<br>Share scan templates via device cloning   |

|   |   |
|---|---|
| <b>Network Protocols</b>                      | FTP via TCP/IP<br>Microsoft SMB via TCP/IP<br>NetWare, HTTP and HTTPS   |
| <b>File Formats</b>                           | Color TIFF (TIFF 6.0 or TTN2 with JPEG, LZW)<br>Black and White TIFF (G3MH, G4 MMR compression - single or multiple pages)<br>PDF or PDF/A (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for B/W and within MRC))<br>JPEG<br>XPS<br>Searchable PDF, PDF/A, XPS<br>Encrypted / Password Protected PDF (for Workflow Scanning)<br>Linearized PDF   |
| <b>Document Management Fields (Metadata)</b>  | Features only available in Network Scan to File Templates: <ul style="list-style-type: none"> <li>• 1-6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata Field consists of field name, display at the LUI or not, default value and other configurations</li> <li>• Customized fields viewed on user interface</li> <li>• Variable data entered using virtual keyboard at device</li> </ul> |
| <b>Scan Features</b>                          | Mixed size originals<br>Bound originals<br>Edge erase<br>Reduction/enlargement<br>Scan Build Job<br>Compression Quality/File Size Control<br>Original type (photo and text, photo, text, map, newspaper/magazine)<br>Auto Background and Shadow Suppression<br>Size for size (for mixed size originals)   |
| <b>Supported Scan Destinations (Standard)</b> | Scan to network server<br>Scan to USB Drive<br>Scan to Email<br>Scan to client (SMB or FTP)<br>Scan to Mailbox<br>Scan to Secure FTP<br>Scan to Home  |
| <b>Supported Scan Destinations (Optional)</b> | Scan to application<br>Scan to Microsoft Exchange 2000 Web Folders<br>Scan to PC Desktop (Professional and SE)<br>SMARTsend®<br>ScanFlowStore<br>ScanSoft PaperPort<br>ScanSoft OmniPage<br>Various Xerox® Business Innovation Partner Solutions  |
| <b>Scan to USB</b>                            | Supports walk-up scan to USB via Type A USB port  |
| <b>Authentication</b>                         | Authentication mechanism <ul style="list-style-type: none"> <li>• Network ID <ul style="list-style-type: none"> <li>- Supports Kerberos (UNIX / Windows Server 2003 / Windows Server 2008)</li> <li>- SMB (Windows 2000 / Windows Server 2003 / Windows Server 2008)</li> <li>- NDS</li> <li>- LDAP</li> </ul> </li> <li>• Xerox® Secure Access Unified ID System®</li> <li>• CAC / PIV</li> <li>• Locally on device (internal database)</li> </ul>                 |
| <b>Scan to Email (Standard)</b>               |   |
| <b>Directory Access</b>                       | Address list via LDAP (Exchange/Notes/Domino)<br>Downloaded address list (comma-separated file format)  |



|   |  |   |
|---|--|---|
| <b>Scan Features</b>                                      | Email signatures (6 lines each of 128 character max), email message body (user configurable), email CWIS confirmation sheet options<br>Scan to Email s/MIME Encryption (with CAC option)<br>Auto send to self  |   |
| <b>Network Scanning – Software Solutions</b>              |  |   |
| <b>Xerox® Scan to PC Desktop® Professional (optional)</b> | A desktop offering that provides advanced document imaging, archiving, editing and organization tools: <ul style="list-style-type: none"> <li>• Nuance PaperPort Professional image viewing and file management software: <ul style="list-style-type: none"> <li>– Complete PDF functionality</li> <li>– Secure PDF workflow of all scanning applications</li> </ul> </li> <li>• Nuance OmniPage Pro Office (for desktop/client installation) – Professional OCR software for digital archiving and document conversion</li> <li>• Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre to individual desktops. Also includes email inbox polling capability</li> </ul>  |   |
| <b>Xerox® SMARTsend® (optional)</b>                       | Server based document routing software that supports multiple scan-enabled multifunctional systems (up to 250 per server): <ul style="list-style-type: none"> <li>• Enables transformation, distribution and routing of scanned documents – with features like LDAP and auto discovery</li> <li>• Workflow creation via Web browser-based task creation (destinations, devices, document attributes – 20 file types including searchable PDF, workflow settings, workflow summary)</li> <li>• Scan to File Destinations: email, Novell NetWare folder, network folder, SMB folder, FTP, Microsoft Exchange 2000 Web folders, Web URL, remote printers</li> <li>• Scan to Document Repository Destinations: DocuShare, Domino, Domino.doc, Microsoft SharePoint</li> <li>• Workflow initiation via device scanning user interface (template selection at device UI)</li> </ul>  |   |
| <b>Xerox® SMARTsend® Professional (optional)</b>          | Everything in Xerox® SMARTsend, plus: <ul style="list-style-type: none"> <li>• Workflow initiation via Paperware (Scan cover sheets)</li> <li>• Server-based Optical Character Recognition (OCR)</li> <li>• Adding Metadata</li> <li>• Scan to Internet fax file destination</li> </ul>  |   |
| <b>Security</b>   |  |   |
| <b>Features</b>   | <p>144 CAC/PIV Card Support (2048 bit certificate key)<br/>Expanded Authentication</p> <ul style="list-style-type: none"> <li>• Network authentication to access device and/or device services via: <ul style="list-style-type: none"> <li>- Kerberos (UNIX / Windows Server 2003 / Windows Server 2008)</li> <li>- SMB (Windows 2000 / Windows Server 2003 / Windows Server 2008)</li> <li>- NDS</li> <li>- LDAP</li> </ul> </li> <li>• Xerox Secure Access</li> <li>• Local Authentication (internal database)</li> <li>• Smart Card authentication with CAC/PIV</li> </ul> <p>Secure Data</p> <ul style="list-style-type: none"> <li>• Digitally signed PDF (only via CAC)</li> <li>• Encrypted Scan to Email (only via CAC)</li> <li>• Password Protected PDF (via Workflow scanning; not Scan to Email)</li> <li>• Secure Print (up to 10 digit PIN)</li> <li>• Immediate Image Overwrite</li> <li>• On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk</li> <li>• 256 bit Hard Disk Encryption</li> </ul> | <p>Expanded Authorization</p> <ul style="list-style-type: none"> <li>• SA access based on network credentials</li> <li>• Authorization per user per service</li> <li>• User Permissions required to access Print and Print Features (e.g. color access, or time restrictions) reflects in the print driver</li> </ul> <p>Secure Network Access</p> <ul style="list-style-type: none"> <li>• IP Filter</li> <li>• IPsec</li> <li>• IPv6 Ready</li> <li>• Secure print-channel encryption with IPsec</li> <li>• Secure scanning and network management (SSL, SNMPv3)</li> <li>• Secure Web Page via SSL</li> <li>• Secure web interface via HTTPs</li> <li>• 802.1X</li> </ul> <p>Device Security</p> <ul style="list-style-type: none"> <li>• Port disablement including USB ports</li> </ul> <p>FIPS 140-2 Compliant Encryption</p> <p>Audit Log</p> <p>Hide Print Job Names</p> <p>Secure Print Separate Queue</p> <p>My Jobs view</p> <p>Common Criteria EAL2+ conformant with 2600.2 protection profile for hardcopy devices</p> |
| <b>Xerox® Secure Access Unified ID System® (Optional)</b> | The Xerox® Secure Access Unified ID System USB card reader configuration eliminates the need for the Authentication Device (also known as the flat box controller). The USB card reader connects directly to the device controller eliminating the need for a second IP address. Device plug-ins must be installed to enable the device functionality. The plug-ins are available at the Xerox® Secure Access Unified ID System and WorkCentre 7500 series download pages on <a href="http://www.xerox.com">www.xerox.com</a> .<br>Secure Access is compatible with Scan to Home.  |   |

| Fax  |   |
|--|---|
| <b>Network Server Fax Features</b>   |   |
| <b>Compatibility</b>   | ITY (CCITT) group 3<br>Various Xerox Business Innovation Partner Solutions  |
| <b>Maximum Scan Area</b>   | 11 x 17 in. (A3)  |
| <b>Fax Send Features</b>   | One- or two-sided scanning (up to 11 x 17 in. – A3)<br>Phone number entry<br>Add to send list (50 numbers maximum)<br>Delay send (specific time) Original type (photo, text or photo and text)<br>Build Job<br>Speed Dial   |
| <b>Fax Print Features</b>  | One- or two-sided printing<br>Staple on/off<br>Secure print on/off  |
| <b>Transmission Resolution</b>   | Superfine - 400 x 200 dpi (Scan at 600 x 600 dpi)<br>Fine - 200 x 200 dpi<br>Standard - 200 x 100 dpi   |
| <b>Fax Options – Internet Fax (Standard)</b>   |   |
| <b>Capability</b>  | Direct print-ready document transmission to remote Internet Fax machines or email clients (SMTP)<br>Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients   |
| <b>Address Directory Access</b>  | Send: Multi-page TIFF, PDF, PDF/A<br>Receive: TIFF, MTIFF, PDF, PDF/A, PS, text, PCL, PRN, JPEG   |
| <b>Resolution</b>  | 600 x 600 dpi<br>400 x 400 dpi<br>300 x 300 dpi<br>200 x 200 dpi<br>200 x 100 dpi<br>150 x 150 dpi<br>100 x 100 dpi<br>72 x 72 dpi<br>Bit Dept: 1-bit (black and white)   |
| <b>Network Protocols</b>   | SMTP (send)<br>POP3 (receive)   |
| <b>Compliance</b>  | ITU-T T.37 compliant  |
| <b>Fax Options – Walk-up Option - One or Two line (Optional; Customer installable)</b> |   |
| <b>Compatibility</b>   | ITY (CCITT) Group 3   |
| <b>Speed/Modems</b>  | One or Two V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time<br>ISDN via third-party adapter  |
| <b>Compression/Speed</b>   | MH/G3, MMR/G4   |
| <b>Fax Send Features</b>   | LAN Fax (fax from print driver)<br>Auto fax transmission reduction<br>Page-by-page job status at the machine<br>Delay start<br>Automatic memory resend<br>Automatic cover sheets<br>Broadcast<br>Booklet Scan<br>PSTN Fax<br>Build Job<br>Speed Dial<br>Searchable Dial Directory |

|  |   |
|--|---|
| <b>Fax Receive Features</b>                                      | One- or two-sided printing<br>Stapled or unstapled, hole punch<br>Receive print mode – Manual (size, margin, stock, header) / Auto<br>Output tray selection<br>Junk Fax prevention<br>Up to 200 password protected mailboxes  |
| <b>Fax Forward</b>   | Forward to Email or SMB Location<br>Fax forward on receive only   |
| <b>Fax Reports</b>   | Activity<br>Dial directory<br>Group directory<br>Transmission confirmation<br>Pending fax<br>Options report<br>On demand overwrite report   |
| <b>Auto Dialing</b>  | <b>Speed Dials:</b><br>1,000 total (one- or two-line options)<br><br><b>Group Dials:</b><br>Up to 200 groups with up to 400 recipients per group (one- or two-line options)<br><br><b>Auto Redial:</b><br>Up to 14 attempts<br>1 to 25 minute intervals<br>Batch send (up to memory capacity)   |
| <b>Device Management</b>   |   |
| <b>Management Support</b>  | SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP<br>MIB access (IETF-MIBII RFC 1213), Host Resources<br>MIB RFC 2790, Printer MIB RFC 1759 v.2  |
| <b>Xerox® CentreWare® Web</b>                                    | A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system: <ul style="list-style-type: none"> <li>• Works with any SNMP-managed printer from any manufacturer.</li> <li>• Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management.</li> <li>• Requires Windows XP, 2000 (Professional or Advanced Server) or Windows 2003 and Internet Explorer 6.0 and higher</li> </ul> |
| <b>Xerox® CentreWare for Tivoli® NetView®</b>                    | Provides for the identification of Xerox® WorkCentre multifunction systems in the general discovery performed by Tivoli NetView   |
| <b>Novell NDPS/NEPS</b>  | Server gateway application: centralized management tool   |
| <b>Xerox® CentreWare® for Unicenter TNG®</b>                     | Provides added identification to the general discovery performed by Unicenter TNG and the ability to see the WorkCentre under a Unicenter TNG Business Process View   |
| <b>Xerox® CentreWare® for Microsoft Management Console (MMC)</b> | CentreWare MC Snap-in supports printer discovery and management via a Microsoft Management Console (MMC) link to an embedded Web server. It is a general-purpose management display framework for hosting administrative tools.   |
| <b>Xerox® CentreWare for HP® OpenView®</b>                       | Provides for the identification of Xerox® WorkCentre multifunction systems in the general discovery performed by HP Openview<br>Provides traps and message updates to the Open View alarm browser and the ability to launch CentreWare Internet Services for device management directly from OpenView   |

|  |   |
|--|---|
| <p><b>Xerox® Device Manager</b></p>  | <p>Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides:</p> <ul style="list-style-type: none"> <li>• Device monitoring and troubleshooting</li> <li>• Extensive reporting and discovery of new devices</li> <li>• Usage collection, chargeback and billing capabilities</li> </ul>  |
| <p><b>Xerox® Device Types for SAP R/3 Environment</b></p> <p>Information available at <a href="http://www.xeroxofficesapsolutions.com">www.xeroxofficesapsolutions.com</a></p>           | <p>Simplifies printing in SAP R/3 environments by providing users of SAP R/3 3.x, 4.x, 4.5x, 4.6x, SAP Enterprise 4.7x, ERP applications with enhanced WorkCentre printing functionality (PostScript and PCL):</p> <ul style="list-style-type: none"> <li>• One- to two-sided printing</li> <li>• Finishing provides single or dual stapling</li> <li>• Tray pull location from any tray</li> <li>• Number of copies – provide the ability to print multiple copies</li> <li>• Paper Type and color – provide ability to select different paper types and paper colors, such as transparency, red, etc.</li> <li>• Print security via PIN ID capability</li> <li>• Network Accounting – Provides capability to add Network Accounting User IDs to SAP print jobs</li> <li>• Printer banner sheet – Provide the ability to enable/disable printer banner sheets</li> <li>• Barcode printing – Xerox standard PostScript device types available at <a href="http://www.xeroxofficesapsolutions.com">www.xeroxofficesapsolutions.com</a> supports Intelligent Barcode Printing with Xerox Barcode Pro PS. This Barcode Pro PS can be purchased at <a href="http://www.font.net">www.font.net</a>.</li> <li>• Unicode Font Kit</li> </ul> |
| <p><b>Xerox® SAP R/3 Intelligent Barcode Utility (optional)</b></p> <p>Information available at <a href="http://www.xeroxofficesapsolutions.com">www.xeroxofficesapsolutions.com</a></p> | <p>Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer on the SAP R/3 4.1x, 4.5x, 4.6x and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox PostScript Device Types for SAP R/3 environment and Xerox Font Center Barcode Fonts. Utility enables automated checksum calculation, placement of start/stop characters, encoding of data string and data compression.</p>  |
| <p><b>Xerox® Barcode Pro PS (optional)</b></p> <p>Information available at <a href="http://www.xeroxofficesapsolutions.com">www.xeroxofficesapsolutions.com</a></p>                      | <p>Enables intelligent PostScript printing on Xerox multifunction systems by storing Xerox software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP R/3 client or mainframe) that supports PostScript printing. Automatically calculates the check digit, places start/stop and middle bar characters in the data string, compresses and encodes the data string, and rotates the barcode through 90 or 270 degrees.</p>  |
| <p><b>CentreWare Internet Services – Integrated Web Pages Provided by the Device</b></p>   |   |
| <p><b>Device Status</b></p>  | <p>Web server embedded in Network Controller:</p> <ul style="list-style-type: none"> <li>• Tray status/contents</li> <li>• Consumables status</li> <li>• Alerts</li> </ul>  |
| <p><b>Job Submission</b></p>   | <p>Print ready files: PS, PCL, TIFF, PDF, JPG, XPS<br/> Output feature selection (2-sided, output color, collate, orientation, staple, hole punch, folding, output destination)<br/> Delivery options (Immediate, sample set, delay and secure, Save job or reprint)</p>  |
| <p><b>Device Administration</b></p>  | <p>Allows simple, remote installation setting of configuration options and management of the device</p>   |
| <p><b>Browsers</b></p>   | <p>Netscape 7.x, 9.x<br/> Internet Explorer 6.x, 7.x, 8.x<br/> Safari 3.0-3.2, 4.0.3<br/> Mozilla Firefox 2.x, 3.5, 3.6.3<br/> Opera 9.x, 10<br/> Chrome 1.0, 4.1, 5.x</p>  |
| <p><b>Support</b></p>  | <p>Install print/scan drivers and online support available via web page</p>   |
| <p><b>Languages Supported</b></p>  | <p>International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish or Russian</p>   |

| Smart eSolutions  |  |
|---|--|
| <b>MeterAssistant®</b>  | Automates the process of collecting and submitting meter reads for tracking and billing of Xerox device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.<br>Device Direct or via Smart eSolutions Client for Windows or via CentreWare® Web.  |
| <b>SuppliesAssistant®</b>                                       | Automatically orders supplies for Xerox output devices based on actual usage, eliminating the need to manually manage supplies inventory.<br>Device Direct or via Smart eSolutions Client for Windows or via CentreWare Web.   |
| <b>MaintenanceAssistant</b>                                     | Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.<br>Device Direct   |
| <b>Online Support Assistant</b>                                 | Xerox® Online Support keeps you up and running by providing instant access to searchable online help right at the WorkCentre 7500 series multifunction printer's front panel. You get the same information our Product Support Specialists use when resolving printer problems, assisting with error codes, print quality, media jams, software installation, and more.  |
| EFI Fiery Network Controller with System Software 9e (Optional) |  |
| <b>Processor</b>  | 2.66 GHz, Intel Core 2 Duo E5300   |
| <b>Memory (ESS)</b>   | 1 GB   |
| <b>System Disk</b>  | 160 GB   |
| <b>Print Languages (PDL)</b>                                    | PostScript v 3019  |
| <b>Features</b>   | Command WorkStation capability via a PC or MAC (customer to provide) with Queue Management<br>Job Preview<br>Job Merge<br>Change Job Properties<br>Pantone Color Tables<br>Expert Color Settings: Profile, Rendering and Simulation<br>ColorWise Pro Tools – calibration support, color editor, profile manager<br>FreeForm – Variable Data capabilities<br>Booklet Maker 4.0 – booklet wizard to create booklets<br>Print from USB flash drive<br>Paper Catalog<br>Secure Erase |
| <b>Connectivity</b>   | 10Base-T/100Base-TX/1000Base-T Ethernet  |
| <b>Optional</b>   | SeeQuence Suite (Impose & Compose)<br>Mini-bundle (Spot On, Auto Trapping, Hot folders, Virtual Print)<br>A la Carte Spot On, Auto Trapping, Hot folder/Virtual Printers)  |
| Accounting  |  |
| Accounting – Xerox® Standard Accounting (Standard)              |  |
| <b>Tracking</b>   | Copy, Print, Fax and Scan usage  |
| <b>Accounting</b>   | Up to 2,500 User accounts (User ID)<br>Up to 500 General accounts (Client)<br>Up to 500 Group accounts (Department)  |

|   |  |
|---|--|
| <b>Features</b>   | <p>Enable/disable via the Web User Interface or the device control panel in tools, Administrator can manage the feature remotely via the Web User Interface</p> <p>Data can be exported via a CSV file</p> <p>Supports entering Xerox® Standard Accounting ID into the print driver when submitting a print job</p>  |
| <b>Accounting Options – Network Accounting – Third Party Enablement</b> |  |
|   | <ul style="list-style-type: none"> <li>Enhanced network accounting with up to the minute data on how the WorkCentre system is being used</li> <li>Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax</li> <li>Various options are available through Xerox® Alliance Partner solutions. For details visit <a href="http://www.xerox.com">www.xerox.com</a></li> <li>Security enhancements with the addition of HTTPS protocol support</li> <li>WorkCentre requests account authentication from 3rd-party server enabling larger databases of users and accounts</li> <li>Accept Authentication Login at control panel and pass to 3rd party Networking Account</li> <li>Interface with 3rd party accounting terminal for accounting user interface</li> </ul> |
| <b>Device Specifications</b>  |  |
| <b>Monthly Duty Cycle</b>   |  |
|   | <p>WorkCentre 7525: up to 75,000 pages/month</p> <p>WorkCentre 7530: up to 90,000 pages/month</p> <p>WorkCentre 7535: up to 110,000 pages/month</p> <p>WorkCentre 7545: up to 200,000 pages/month</p> <p>WorkCentre 7556: up to 300,000 pages/month</p>  |
| <b>Basic Configurations</b>   |  |
|   | <p>1 Tray Option</p> <p>3 Tray Option</p> <p>High Capacity Tandem Tray Option</p>  |
| <b>Accessories</b>  |  |
| <b>Optional</b>   | <p>High Capacity Feeder</p> <p>Envelope Tray (Replaces Tray 1)</p> <p>Integrated Office Finisher (optional with 7525/7530/7535 only)</p> <p>Office Finisher LX</p> <p>Booklet Maker for Office Finisher LX</p> <p>Hole Punch for Office Finisher LX</p> <p>Professional Finisher</p> <p>Convenience Stapler (includes Work Surface)</p> <p>Common Access Card Enablement Kit</p> <p>Xerox® Secure Access Unified ID System® (with USB Card Reader)</p> <p>EFI® Fiery Network Controller</p> <p>Foreign Device Interface</p> <p>Xerox® Copier Assistant®</p> <p>Walk up Fax (One- or Two-line options, includes LAN Fax)</p> <p>Xerox® Scan to PC Desktop®</p> <p>ScanFlowStore®</p> <p>Xerox® Unicode International Print Kit</p>  |
| <b>Foreign Device Interface (FDI) (Optional)</b>                        | <p>Interface to third party access control devices, coin machines, card readers</p> <p>Support a variety of vending stations available through the Xerox® Custom Application Service</p>   |
| <b>Accessibility Option</b>   | <p>Xerox® Copier Assistant® (XCA) Software provides a PC-based alternative to the user interface touch screen. Used in conjunction with a customer-supplied PC attached via the USB port, this software supports text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features.</p> <p>Section 508 compliant. For more information, visit <a href="http://www.xerox.com">www.xerox.com</a>.</p>   |
| <b>Electrical Requirements</b>  |  |
| <b>North America</b>  | <p>Voltage : 110 –127 VAC +/- 10 %</p> <p>Frequency: 50/60 Hz +/- 3 %, 15 A</p> <p>Power Consumption: 1.108 KVA maximum printing continuously (120V)</p>   |

|  |  |                   |                     |                   |
|--|--|-------------------|---------------------|-------------------|
| <b>Europe</b>  | Voltage : 220-240 VAC +/- 10 %<br>Frequency: 50/60 Hz +/- 3 %, 10 A<br>Power Consumption: 1.203 KVA maximum printing continuously (240V), 1.760 KVA maximum printing continuously (220)  |                   |                     |                   |
| <b>Power Consumption (Base IOT)</b>                        |  |                   |                     |                   |
| <b>Running (Average)</b>                                   | 984 watts/hour   |                   |                     |                   |
| <b>Standby Mode</b>  | 130 watts/hour   |                   |                     |                   |
| <b>Low Power Mode</b>                                      | 82 watts/hour  |                   |                     |                   |
| <b>Auto Off / Sleep mode</b>                               | 9.1 watts/hour (Default time to Sleep mode = 2 minutes)  |                   |                     |                   |
| <b>Warm-up</b>   | 2 minutes, 59 seconds  |                   |                     |                   |
| <b>Low Power Recovery</b>                                  | < 9 seconds  |                   |                     |                   |
| <b>Operating Environment</b>                               |  |                   |                     |                   |
| <b>Required Temperature Range</b>                          | 50° to 82° F (10° to 28° C)  |                   |                     |                   |
| <b>Required Relative Humidity</b>                          | 15 % to 85 %   |                   |                     |                   |
| <b>Sound Power Levels</b>                                  | Operating 7.5 B(A), Standby: 3.6 B(A)  |                   |                     |                   |
| <b>Sound Pressure Levels</b>                               | Operating: 58 dB(A), Standby: 18 dB(A)   |                   |                     |                   |
| <b>Dimensions and Weight</b>                               | <b>Width</b>   | <b>Depth</b>      | <b>Height</b>       | <b>Weight</b>     |
| <b>Base Configuration</b>                                  | 41.9 in. / 1,064 mm  | 27 in. / 685 mm   | 44.4 in. / 1,127 mm | 308 lbs. / 140 kg |
| <b>With Integrated Office Finisher</b>                     | 44.4 in. / 1,129 mm  | 27 in. / 685 mm   | 44.4 in. / 1,127 mm | 334 lbs. / 152 kg |
| <b>With Office Finisher LX (with Booklet Maker)</b>        | 65.6 in. / 1,666 mm  | 27.4 in. / 695 mm | 44.4 in. / 1,127 mm | 390 lbs. / 177 kg |
| <b>With Professional Finisher</b>                          | 75.7 in. / 1,922 mm  | 27 in. / 685 mm   | 44.4 in. / 1,127 mm | 502 lbs. / 228 kg |
| <b>With Professional Finisher and High Capacity Feeder</b> | 75.7 in. / 1,922 mm  | 27 in. / 685 mm   | 44.4 in. / 1,127 mm | 564 lbs. / 256 kg |
| <b>Certifications</b>                                      |  |                   |                     |                   |
|  | FCC Class A Compliant (US), ICES Class A Compliant (Canada)<br>TUV Listed (UL 60950-1, Second Edition)<br>CB Certified (IEC 60950-1, Second Edition)<br>2006/95/EC (Europe)<br>2005/32/EC (Europe)<br>2004/108/EC (Europe)<br>199/5/EC (Europe)<br>ENERGY STAR®<br>GOST<br>NOM<br>Blue Angel<br>Environmental Choice<br>CE Certification<br>Common Criteria (IEEE 2600.2 standard) |                   |                     |                   |

# Xerox® WorkCentre® 7525/7530/7535/7545/7556

| Supplies                   | Description  | Yield                | Order Number |
|----------------------------|--|----------------------|--------------|
| Toner Cartridges (Metered) | Black  | 26,000 <sup>3</sup>  | 006R01509    |
|                            | Cyan   | 15,000 <sup>3</sup>  | 006R01512    |
|                            | Magenta  | 15,000 <sup>3</sup>  | 006R01511    |
|                            | Yellow   | 15,000 <sup>3</sup>  | 006R01510    |
| Toner Cartridges (Sold)    | Black  | 26,000 <sup>3</sup>  | 006R01513    |
|                            | Cyan   | 15,000 <sup>3</sup>  | 006R01516    |
|                            | Magenta  | 15,000 <sup>3</sup>  | 006R01515    |
|                            | Yellow   | 15,000 <sup>3</sup>  | 006R01514    |
| Transfer Belt Cleaner      | 1 Assembly   | 160,000 <sup>3</sup> | 001R00613    |
| Second Bias Transfer Roll  | 1 Assembly   | 200,000 <sup>3</sup> | 008R13064    |
| Staple Cartridge           | for Integrated Office Finisher, Office Finisher LX, Professional Finisher and Convenience Stapler (1 cartridge per carton) | 5,000 each cartridge | 008R12964    |
| Staple Cartridge           | for Office Finisher LX Booklet Maker (8 cartridge per carton)  | 2,000 each cartridge | 008R12897    |
| Staple Cartridge           | for Professional Finisher Booklet Maker (1 cartridge per carton)   | 5,000 each cartridge | 008R12925    |
| Staple Refills             | for Integrated Office Finisher, Office Finisher LX, Professional Finisher and Convenience Stapler (3 refills per carton)   | 5,000 each refill    | 008R12941    |
| Smart Kits®                | Description  | Yield                | Order Number |
| Drum Cartridge             | 1 Cartridge  | 125,000 <sup>3</sup> | 013R00662    |
| Waste Toner Container      | 1 Cartridge  | 43,000 <sup>3</sup>  | 008R13061    |

<sup>3</sup> Approximate pages. Declared Yield based on 5 page job size, 30% color and 70% Black and white ratio, using letter-/A4-size media. Yield will vary based on media size, image area coverage, media orientation and usage patterns.

