

Xerox® WorkCentre® 7525/7530/7535/7545/7556 Multifunction Printer



WorkCentre 7500 series shown with 1 Tray Option and Work Surface



WorkCentre 7500 series shown with 3 Tray Option



WorkCentre 7500 series shown with High Capacity Tandem Tray Option, Work Surface and Integrated Office Finisher (optional only with 7525/7530/7535)



WorkCentre 7500 series shown with High Capacity Tandem Tray Option, Work Surface and Office Finisher LX with Booklet Maker Option



WorkCentre 7500 series shown with High Capacity Tandem Tray Option, Work Surface and Professional Finisher

System Specifications					
Output Speed (Printing and Copying)	WorkCentre 7525	WorkCentre 7530	WorkCentre 7535	WorkCentre 7545	WorkCentre 7556
Color	Up to 25 ppm	Up to 30 ppm	Up to 35 ppm	Up to 45 ppm	Up to 50 ppm
Black and White	Up to 25 ppm	Up to 30 ppm	Up to 35 ppm	Up to 45 ppm	Up to 55 ppm
Functions					
Standard	Copy, Print (Adobe® PostScript® 3™, PCL, XML Paper Specifications (XPS), PDF, Print from USB) Scan Kit (Scan to USB, Email, Mailbox, Network Folder, Home), Fax (Server Fax integration, Internet Fax), Data Security (Hard Disk encryption, Disk Overwrite), Network Accounting, EIP				
Optional	Walk-up Fax (One- or Two-line), ScanFlowStore®, SMARTsend®, CAC / Personal Identification Verification (PIV), Xerox Secure Access Unified ID System®, EFI® Fiery Workflow				
Specifications					
Processor	1.5 GHz				
Memory	2 GB system plus 1 GB page memory				
Hard Drive	160 GB				
Connectivity	10/100/1000Base-T Ethernet High-Speed USB 2.0 Wireless Ethernet 802.11b (via third-party adapters)				
USB Port	PC Interface for Xerox® Copier Assistant® via USB Type B port Software upgrade via USB Type A port USB Print and Scan				

Control Panel Languages	Languages: (Select from 18 languages for user interface – International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian or Romanian)				
Copy					
First-Copy-Out Time (Letter-size/A4, from Platen to Center Tray)	WorkCentre 7525	WorkCentre 7530	WorkCentre 7535	WorkCentre 7545	WorkCentre 7556
Color	As fast as 13.2 seconds	As fast as 10.9 seconds	As fast as 11.0 seconds	As fast as 7.8 seconds	As fast as 7.2 seconds
Black and White	As fast as 11.1 seconds	As fast as 8.7 seconds	As fast as 8.6 seconds	As fast as 6.6 seconds	As fast as 5.8 seconds
Copy Specifications					
Sides (input:output)	1-1, 1-2, 2-2, 2-1				
Quantity	1 to 9,999				
Resolution (max)	Scan at 600 x 600 dpi, output at 1200 x 2400 dpi				
Reduction/Enlargement	Variable Zoom from 25% - 400% in 1% increments				
Concurrency	Program-ahead to allow job to be initiated while initial job is processed (Copy, Print, Fax and Scan)				
Basic Copy Features & Options	Collation Automatic 2-sided/Duplex Auto Reduction & Enlargement to fit selected paper size Hole Punching Booklet Creation Stapling Large Job Interrupt Auto Paper Select Authentication for Services (i.e. Color Copy) Auto Tray Switching Features Help (Intuitive text and graphic descriptions)				
Imaging Copy Features	Image Quality: <ul style="list-style-type: none"> • Original Type Selection: Photo & Text, Photo, Text, Newspaper/Magazine, Inkjet Original, Maps. • Image Options: Lighten/Darken, Sharpness, Saturation. • Image Enhancement: Auto Background Suppression, Auto and Manual Contrast. • Color Effects: Off, Single Color, Lively, Bright, Warm, Cool. • Color Balance: Normal, Basic Color Balance, Advanced Color Balance Book Copying/Bound Copying Edge Erase Single Color Repeat Image Mixed Size Original Image Shift (with Auto Center option) Image Shift Preset: Support for 3 Preset Options Annotation and Bates™ stamping (with color capability and font size adjustment)				
Output Copy Features	Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Build Job: (Enables page-level programming and also lets you proof each section or delete last section as the job is built) Transparencies Dividers (blank) Multi-up (up to 15 columns by 15 rows) Invert Image (negative or mirror image) Sample Set Job Settings Save Job Settings				

Paper Handling	
Duplex Automatic Document Feeder	
Capacity ¹	110 sheets
Speed	up to 70 images per minute mono and color
Paper Sizes Sensed	5.5 x 8.5 in. to 11 x 17 in. / A5 to A3
Weights	16 lb bond to 32 lb bond (50 gsm to 128 gsm)
Bypass Tray	
Capacity ¹	100 sheets
Sizes	Custom sizes up to 12.6 x 19 in. / 320 x 483 mm
Weights	16 lb bond to 110 lb cover (55 to 300 gsm)
Types	Plain Bond Lightweight Heavyweight Extra Heavyweight Extra Heavyweight Plus Gloss Heavyweight Gloss Extra Heavyweight Gloss Labels Transparencies Custom Envelopes
1 Tray Option (Includes Tray 1 and Tray 2)	
Capacity ¹	Tray 1: 520 sheets Tray 2: 520 sheets
Sizes	Tray 1: Custom Sizes from 5.5 x 7.5 in. SEF to 11.7 x 17 in. SEF / 140 x 182 mm to 297 x 432 mm Tray 2: Custom Sizes from 5.5 x 7.5 in. SEF to 12.6 x 18 in. SEF / 140 x 182 mm to 320 x 457 mm
Weights	16 lb bond to 140 lb index (60 to 256 gsm)
Types	Plain Bond Heavyweight Extra Heavyweight Gloss Heavyweight Gloss Labels Transparencies Custom
3 Tray Option (Includes Trays 1-4)	
Capacity ¹	Trays 1-4: 520 sheets each tray
Sizes	Tray 1: Custom Sizes from 5.5 x 7.5 in. SEF to 11.7 x 17 in. SEF / 140 x 182 mm to 297 x 432 mm Trays 2-4: Custom Sizes from 5.5 x 7.5 in. SEF to 12.6 x 18 in. SEF / 140 x 182 mm to 320 x 457 mm
Weights	16 lb bond to 140 lb index (60 to 256 gsm)

¹ Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

Types	Plain Bond Heavyweight Extra Heavyweight Gloss Heavyweight Gloss Labels Transparencies Custom
High Capacity Tandem Tray Option	
Capacity¹	Tray 1: 520 sheets Tray 2: 520 sheets Tray 3: 867 sheets Tray 4: 1,133 sheets
Sizes	Tray 1: Custom Sizes from 5.5 x 7.5 in. SEF to 11.7 x 17 in. SEF / 140 x 182 mm to 297 x 432 mm Tray 2: Custom Sizes from 5.5 x 7.5 in. SEF to 12.6 x 18 in. SEF / 140 x 182 mm to 320 x 457 mm Trays 3-4: Standard Sizes: 7.25 x 10.5 in., 8.5 x 11 in. LEF / A4
Weights	16 lb bond to 140 lb index (60 to 256 gsm)
Types	Plain Bond Heavyweight Extra Heavyweight Gloss Heavyweight Gloss Labels Transparencies Custom
High Capacity Feeder (HCF) (Optional with 3 Tray Option or High Capacity Tandem Tray Option)	
Capacity¹	2000 sheets
Sizes	Standard Sizes: 7.25 x 10.5 in., 8.5 x 11 in. LEF / A4
Weights	16 lb bond to 140 lb index (55 to 256 gsm)
Envelope Tray (Optional - Replaces Tray 1)	
Capacity¹	Up to 60 envelopes
Sizes	#10 Commercial (9.25 x 4.125 in.), Monarch, DL, C5 Custom sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in. (98 x 148 mm to 162 x 241 mm)
Weights	20 lb bond to 24 lb bond (75 to 90 gsm)
Total Capacity	
Device Total Capacity	5,140 sheets
Paper Output / Finishing	
Output Trays (Standard)	
Stacking Trays¹	Dual Offset Catch Tray – up to 250 sheets each Left-side Face up Tray – up to 100 sheets

¹ Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

Output – Integrated Office Finisher (Optional with 7525/7530/7535)		
Stacking Tray	500 sheets of 20 lb bond (80 gsm) 8.5 x 11 in./A4 or 250 sheets of 20 lb bond (80 gsm) 11 x 17 in./A3	
Sizes	3.5 x 3.9 in. to 11 x 17 in. / 89 x 98 mm to A3	
Weights	16 lb bond to 80 lb cover / 60 to 220 gsm	
Stapling	Single Auto stapling: 50 sheets maximum: Letter/A4/B5-size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal/Tabloid/A3/B4-size sheets (less than 90 gsm or (2) 220 gsm covers)	
Office Finisher LX (Optional)		
Capacity ¹	Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in./A4)	
Sizes	7.2 x 8.3 in. to 11 x 17 in. / 182 x 210 mm to A3	
Weights	16 lb bond to 80 lb cover (60 to 220 gsm)	
Multiposition Stapling	50 sheets of 24 lb bond (90 gsm)	
Hole Punch (Optional)	North America 2-3 Hole Punch	Europe 2-4 Hole Punch
Booklet Maker for Office Finisher LX (Score/Crease, Saddle-stitch Staple) (Optional)		
Capacity	40 booklets (2-15 sheets per booklet – 20 lb/80 gsm or less)	
Sizes	Letter – 8.5 x 11 in. (A4) SEF Legal – 8.5 x 14 in. (216 x 356 mm) SEF Ledger – 11 x 17 in. (A3) SEF	
Saddle-stitch Stapling	2-15 sheets / 8 – 60 page booklet 16 lb bond to 24 lb bond / 60 to 90 gsm	
Score/Crease	1-15 sheets / unstapled	
Professional Finisher (Optional)		
Capacity ¹	Top Tray: 500 sheets of 8.5 x 11 in. / A4 unstapled Stacking Stapling Tray: 1,500 sheets of 8.5 x 11 in. / 11 x 17 in. / A4 / A3 / SRA3 unstapled or 200 stapled sets of 8.5 x 11 in. / A4 or 100 stapled sets of 11 x 17 in. / A3 / SRA3	
Sizes	8 x 10 in. to 12 x 18 in. / B5 to SRA3	
Weights	16 lb bond to 80 lb cover (60 to 220 gsm)	
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb/90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported	
Hole Punch (Standard)	North America 2-3 Hole Punch	Europe 2-4 Hole Punch 4 Hole Swedish Punch (Optional)
Booklet Maker	Saddle-stitch 2 to 15 sheets of 24 lb / 90 gsm or less V-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4, SRA3 supported	
Convenience Stapler (Optional - Includes Work Surface)		
Capacity ¹	50-sheet stapling 5,000 staples Requires a separate outlet	

¹ Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

Print			
Print Controller			
Page Description Languages (PDL) (Standard)	PCL® 6 PCL® 5c Adobe® PostScript® 3™ PDF XPS® HP-GL2™ TIFF		
Print resolution	Print Engine: up to 1200 x 2400 dpi <ul style="list-style-type: none"> • Toner Saver - 600x600 dots per inch, with limits on maximum saturation • Standard - 600x600 dots per inch with 256 halftone levels. • Enhanced - Raster image processing at 600x600 dots per inch with eight bits per pixel. Halftone creation with resolution enhancement and LED marking at 1200x2400 dots per inch with 256 halftone levels. • High Resolution - 1200x1200 dots per inch with 256 halftone levels. 		
Print Features	<table border="0" style="width: 100%;"> <tr> <td style="vertical-align: top; width: 50%;"> Application defaults Banner Sheet enable/disable Bi-directional status Color Options <ul style="list-style-type: none"> • Automatic Color • Vivid Color • Black and White • Custom Color Options <ul style="list-style-type: none"> - Color By Words - Color Correction (allows for different RGB, CMYK, Spot and other specifications) - Color Adjustments (Lightness, Contrast, Saturation, Color cast) Cover selection Delay Print (specific time) Duplex (2-sided) Enhanced Gloss at normal speed User Permissions required to access Print and Print Features (e.g. color access, or time restrictions) reflects in the print driver Finishing <ul style="list-style-type: none"> • Multiple stapling positions • Hole punch • Booklet creation • Fit to new paper size • Saddle stitch with Professional finisher • Output tray selections • Store and recall driver setting Inserts and exception pages Image Options <ul style="list-style-type: none"> • Toner Saver • Resolution options (Standard, High resolution, Enhanced, Toner Saver) • Reduction/Enlargement • Rotate 180 degrees • Margins • Mirrored output </td> <td style="vertical-align: top; width: 50%;"> Job identification (Print ID or Banner, Print ID in margins on first page only or all pages) Job Type <ul style="list-style-type: none"> • Secure, Sample, Delay, Save Layout/Watermark (N-up (16) / Multi-up, Booklet Layout / Finishing, Fit to new paper size) Margins Mirror image N-up Overlays Paper selection by attribute Print calibration Print to Fax (requires optional Fax kit) Sample Set Scaling Secure Print Special Pages (exception page programming (covers, inserts, exception pages) Store and Recall driver settings Store file in folder Sustainability features <ul style="list-style-type: none"> • Xerox Earth Smart settings <ul style="list-style-type: none"> - Duplex - N-up - Turn-off banner and print ID on document - Smart Sample set • Hold All Jobs Transparency separators </td> </tr> </table>	Application defaults Banner Sheet enable/disable Bi-directional status Color Options <ul style="list-style-type: none"> • Automatic Color • Vivid Color • Black and White • Custom Color Options <ul style="list-style-type: none"> - Color By Words - Color Correction (allows for different RGB, CMYK, Spot and other specifications) - Color Adjustments (Lightness, Contrast, Saturation, Color cast) Cover selection Delay Print (specific time) Duplex (2-sided) Enhanced Gloss at normal speed User Permissions required to access Print and Print Features (e.g. color access, or time restrictions) reflects in the print driver Finishing <ul style="list-style-type: none"> • Multiple stapling positions • Hole punch • Booklet creation • Fit to new paper size • Saddle stitch with Professional finisher • Output tray selections • Store and recall driver setting Inserts and exception pages Image Options <ul style="list-style-type: none"> • Toner Saver • Resolution options (Standard, High resolution, Enhanced, Toner Saver) • Reduction/Enlargement • Rotate 180 degrees • Margins • Mirrored output 	Job identification (Print ID or Banner, Print ID in margins on first page only or all pages) Job Type <ul style="list-style-type: none"> • Secure, Sample, Delay, Save Layout/Watermark (N-up (16) / Multi-up, Booklet Layout / Finishing, Fit to new paper size) Margins Mirror image N-up Overlays Paper selection by attribute Print calibration Print to Fax (requires optional Fax kit) Sample Set Scaling Secure Print Special Pages (exception page programming (covers, inserts, exception pages) Store and Recall driver settings Store file in folder Sustainability features <ul style="list-style-type: none"> • Xerox Earth Smart settings <ul style="list-style-type: none"> - Duplex - N-up - Turn-off banner and print ID on document - Smart Sample set • Hold All Jobs Transparency separators
Application defaults Banner Sheet enable/disable Bi-directional status Color Options <ul style="list-style-type: none"> • Automatic Color • Vivid Color • Black and White • Custom Color Options <ul style="list-style-type: none"> - Color By Words - Color Correction (allows for different RGB, CMYK, Spot and other specifications) - Color Adjustments (Lightness, Contrast, Saturation, Color cast) Cover selection Delay Print (specific time) Duplex (2-sided) Enhanced Gloss at normal speed User Permissions required to access Print and Print Features (e.g. color access, or time restrictions) reflects in the print driver Finishing <ul style="list-style-type: none"> • Multiple stapling positions • Hole punch • Booklet creation • Fit to new paper size • Saddle stitch with Professional finisher • Output tray selections • Store and recall driver setting Inserts and exception pages Image Options <ul style="list-style-type: none"> • Toner Saver • Resolution options (Standard, High resolution, Enhanced, Toner Saver) • Reduction/Enlargement • Rotate 180 degrees • Margins • Mirrored output 	Job identification (Print ID or Banner, Print ID in margins on first page only or all pages) Job Type <ul style="list-style-type: none"> • Secure, Sample, Delay, Save Layout/Watermark (N-up (16) / Multi-up, Booklet Layout / Finishing, Fit to new paper size) Margins Mirror image N-up Overlays Paper selection by attribute Print calibration Print to Fax (requires optional Fax kit) Sample Set Scaling Secure Print Special Pages (exception page programming (covers, inserts, exception pages) Store and Recall driver settings Store file in folder Sustainability features <ul style="list-style-type: none"> • Xerox Earth Smart settings <ul style="list-style-type: none"> - Duplex - N-up - Turn-off banner and print ID on document - Smart Sample set • Hold All Jobs Transparency separators		
Print from USB	Allows walk-up printing from Type A USB port on front panel Supports direct printing from computer via Type B USB port		

Print Protocols and Networks	
Operating Systems	Microsoft Windows XP (32- and 64-bit), Windows Server 2003 (32- and 64-bit), Server 2008 (32- and 64-bit), Windows Vista (32- and 64-bit), Windows 7 (32- and 64-bit) Mac OS 10.4 (PPD only) Mac OS 10.5-10.6 (PostScript only) Solaris 9, 10 HP UX 11, 11i AIX 5 Linux RedHat Fedora Core 1-7 Linux RedHat Enterprise Linux 4 SUSE 10.X
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway) AppleTalk®: EtherTalk® Microsoft Windows Networking over IP (Most protocols not in use can be disabled) Bonjour IPv6 Secure FTP
Administrative Protocols	DHCP, BOOTP, SNMP, WINS, DDNS, SLP® v2, HTTP, RARP, DHCP Autonet, SSL, NTP
Fonts	PCL: 94 scalable fonts, line printer and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts
Xerox® Mobile Express Driver® (X-MED)	Makes it easy for mobile users to find, use and manage Xerox and non-Xerox devices in every new location. Plug into a new network, and X-MED automatically discovers available printers and provides status and capability information. Save a list of “favorite” printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT. <ul style="list-style-type: none"> • Printers are automatically discovered • Printer list can be managed based on location • Gives Bi-directional feedback device status, supplies, queue management
Xerox® Global Print Driver® (X-GPD)	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management. <ul style="list-style-type: none"> • Lets IT managers qualify, deploy and manage all print devices on the network using a single driver • Fast and easy installation of new devices improves IT efficiency • Truly universal print driver supports Xerox and non-Xerox printers, PCL and PostScript • Gives Bi-directional feedback device status, supplies, queue management
Scan	
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing concurrent jobs)
Input Speed	Scan at up to 70 ipm color scanning, up to 70 ipm black-and-white – 8.5 x 11 in. / A4 LEF
Resolution	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi 150 x 150 dpi 100 x 100 dpi 72 x 72 dpi Bit Depth: 1-bit (black and white), 8-bit (grayscale), 24-bit (color)
Maximum Scan Area	11 x 17 in. / A3
Scan Template Management	Support 250 scan templates Create device specific CentreWare scan templates Select confirmation sheet options Share scan templates via device cloning

Network Protocols	FTP via TCP/IP Microsoft SMB via TCP/IP NetWare, HTTP and HTTPS
File Formats	Color TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black and White TIFF (G3MH, G4 MMR compression - single or multiple pages) PDF or PDF/A (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for B/W and within MRC)) JPEG XPS Searchable PDF, PDF/A, XPS Encrypted / Password Protected PDF (for Workflow Scanning) Linearized PDF
Document Management Fields (Metadata)	Features only available in Network Scan to File Templates: <ul style="list-style-type: none"> • 1-6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata Field consists of field name, display at the LUI or not, default value and other configurations • Customized fields viewed on user interface • Variable data entered using virtual keyboard at device
Scan Features	Mixed size originals Bound originals Edge erase Reduction/enlargement Scan Build Job Compression Quality/File Size Control Original type (photo and text, photo, text, map, newspaper/magazine) Auto Background and Shadow Suppression Size for size (for mixed size originals)
Supported Scan Destinations (Standard)	Scan to network server Scan to USB Drive Scan to Email Scan to client (SMB or FTP) Scan to Mailbox Scan to Secure FTP Scan to Home
Supported Scan Destinations (Optional)	Scan to application Scan to Microsoft Exchange 2000 Web Folders Scan to PC Desktop (Professional and SE) SMARTsend® ScanFlowStore ScanSoft PaperPort ScanSoft OmniPage Various Xerox® Business Innovation Partner Solutions
Scan to USB	Supports walk-up scan to USB via Type A USB port
Authentication	Authentication mechanism <ul style="list-style-type: none"> • Network ID <ul style="list-style-type: none"> - Supports Kerberos (UNIX / Windows Server 2003 / Windows Server 2008) - SMB (Windows 2000 / Windows Server 2003 / Windows Server 2008) - NDS - LDAP • Xerox® Secure Access Unified ID System® • CAC / PIV • Locally on device (internal database)
Scan to Email (Standard)	
Directory Access	Address list via LDAP (Exchange/Notes/Domino) Downloaded address list (comma-separated file format)

Scan Features	Email signatures (6 lines each of 128 character max), email message body (user configurable), email CWIS confirmation sheet options Scan to Email s/MIME Encryption (with CAC option) Auto send to self	
Network Scanning – Software Solutions		
Xerox® Scan to PC Desktop® Professional (optional)	A desktop offering that provides advanced document imaging, archiving, editing and organization tools: <ul style="list-style-type: none"> • Nuance PaperPort Professional image viewing and file management software: <ul style="list-style-type: none"> – Complete PDF functionality – Secure PDF workflow of all scanning applications • Nuance OmniPage Pro Office (for desktop/client installation) – Professional OCR software for digital archiving and document conversion • Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre to individual desktops. Also includes email inbox polling capability 	
Xerox® SMARTsend® (optional)	Server based document routing software that supports multiple scan-enabled multifunctional systems (up to 250 per server): <ul style="list-style-type: none"> • Enables transformation, distribution and routing of scanned documents – with features like LDAP and auto discovery • Workflow creation via Web browser-based task creation (destinations, devices, document attributes – 20 file types including searchable PDF, workflow settings, workflow summary) • Scan to File Destinations: email, Novell NetWare folder, network folder, SMB folder, FTP, Microsoft Exchange 2000 Web folders, Web URL, remote printers • Scan to Document Repository Destinations: DocuShare, Domino, Domino.doc, Microsoft SharePoint • Workflow initiation via device scanning user interface (template selection at device UI) 	
Xerox® SMARTsend® Professional (optional)	Everything in Xerox® SMARTsend, plus: <ul style="list-style-type: none"> • Workflow initiation via Paperware (Scan cover sheets) • Server-based Optical Character Recognition (OCR) • Adding Metadata • Scan to Internet fax file destination 	
Security		
Features	<p>144 CAC/PIV Card Support (2048 bit certificate key) Expanded Authentication</p> <ul style="list-style-type: none"> • Network authentication to access device and/or device services via: <ul style="list-style-type: none"> - Kerberos (UNIX / Windows Server 2003 / Windows Server 2008) - SMB (Windows 2000 / Windows Server 2003 / Windows Server 2008) - NDS - LDAP • Xerox Secure Access • Local Authentication (internal database) • Smart Card authentication with CAC/PIV <p>Secure Data</p> <ul style="list-style-type: none"> • Digitally signed PDF (only via CAC) • Encrypted Scan to Email (only via CAC) • Password Protected PDF (via Workflow scanning; not Scan to Email) • Secure Print (up to 10 digit PIN) • Immediate Image Overwrite • On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk • 256 bit Hard Disk Encryption 	<p>Expanded Authorization</p> <ul style="list-style-type: none"> • SA access based on network credentials • Authorization per user per service • User Permissions required to access Print and Print Features (e.g. color access, or time restrictions) reflects in the print driver <p>Secure Network Access</p> <ul style="list-style-type: none"> • IP Filter • IPsec • IPv6 Ready • Secure print-channel encryption with IPsec • Secure scanning and network management (SSL, SNMPv3) • Secure Web Page via SSL • Secure web interface via HTTPs • 802.1X <p>Device Security</p> <ul style="list-style-type: none"> • Port disablement including USB ports <p>FIPS 140-2 Compliant Encryption</p> <p>Audit Log</p> <p>Hide Print Job Names</p> <p>Secure Print Separate Queue</p> <p>My Jobs view</p> <p>Common Criteria EAL2+ conformant with 2600.2 protection profile for hardcopy devices</p>
Xerox® Secure Access Unified ID System® (Optional)	The Xerox® Secure Access Unified ID System USB card reader configuration eliminates the need for the Authentication Device (also known as the flat box controller). The USB card reader connects directly to the device controller eliminating the need for a second IP address. Device plug-ins must be installed to enable the device functionality. The plug-ins are available at the Xerox® Secure Access Unified ID System and WorkCentre 7500 series download pages on www.xerox.com . Secure Access is compatible with Scan to Home.	

Fax	
Network Server Fax Features	
Compatibility	ITY (CCITT) group 3 Various Xerox Business Innovation Partner Solutions
Maximum Scan Area	11 x 17 in. (A3)
Fax Send Features	One- or two-sided scanning (up to 11 x 17 in. – A3) Phone number entry Add to send list (50 numbers maximum) Delay send (specific time) Original type (photo, text or photo and text) Build Job Speed Dial
Fax Print Features	One- or two-sided printing Staple on/off Secure print on/off
Transmission Resolution	Superfine - 400 x 200 dpi (Scan at 600 x 600 dpi) Fine - 200 x 200 dpi Standard - 200 x 100 dpi
Fax Options – Internet Fax (Standard)	
Capability	Direct print-ready document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients
Address Directory Access	Send: Multi-page TIFF, PDF, PDF/A Receive: TIFF, MTIFF, PDF, PDF/A, PS, text, PCL, PRN, JPEG
Resolution	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi 200 x 100 dpi 150 x 150 dpi 100 x 100 dpi 72 x 72 dpi Bit Dept: 1-bit (black and white)
Network Protocols	SMTP (send) POP3 (receive)
Compliance	ITU-T T.37 compliant
Fax Options – Walk-up Option - One or Two line (Optional; Customer installable)	
Compatibility	ITY (CCITT) Group 3
Speed/Modems	One or Two V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time ISDN via third-party adapter
Compression/Speed	MH/G3, MMR/G4
Fax Send Features	LAN Fax (fax from print driver) Auto fax transmission reduction Page-by-page job status at the machine Delay start Automatic memory resend Automatic cover sheets Broadcast Booklet Scan PSTN Fax Build Job Speed Dial Searchable Dial Directory

Fax Receive Features	One- or two-sided printing Stapled or unstapled, hole punch Receive print mode – Manual (size, margin, stock, header) / Auto Output tray selection Junk Fax prevention Up to 200 password protected mailboxes
Fax Forward	Forward to Email or SMB Location Fax forward on receive only
Fax Reports	Activity Dial directory Group directory Transmission confirmation Pending fax Options report On demand overwrite report
Auto Dialing	Speed Dials: 1,000 total (one- or two-line options) Group Dials: Up to 200 groups with up to 400 recipients per group (one- or two-line options) Auto Redial: Up to 14 attempts 1 to 25 minute intervals Batch send (up to memory capacity)
Device Management	
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v.2
Xerox® CentreWare® Web	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system: <ul style="list-style-type: none"> • Works with any SNMP-managed printer from any manufacturer. • Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. • Requires Windows XP, 2000 (Professional or Advanced Server) or Windows 2003 and Internet Explorer 6.0 and higher
Xerox® CentreWare for Tivoli® NetView®	Provides for the identification of Xerox® WorkCentre multifunction systems in the general discovery performed by Tivoli NetView
Novell NDPS/NEPS	Server gateway application: centralized management tool
Xerox® CentreWare® for Unicenter TNG®	Provides added identification to the general discovery performed by Unicenter TNG and the ability to see the WorkCentre under a Unicenter TNG Business Process View
Xerox® CentreWare® for Microsoft Management Console (MMC)	CentreWare MC Snap-in supports printer discovery and management via a Microsoft Management Console (MMC) link to an embedded Web server. It is a general-purpose management display framework for hosting administrative tools.
Xerox® CentreWare for HP® OpenView®	Provides for the identification of Xerox® WorkCentre multifunction systems in the general discovery performed by HP Openview Provides traps and message updates to the Open View alarm browser and the ability to launch CentreWare Internet Services for device management directly from OpenView

<p>Xerox® Device Manager</p>	<p>Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides:</p> <ul style="list-style-type: none"> • Device monitoring and troubleshooting • Extensive reporting and discovery of new devices • Usage collection, chargeback and billing capabilities
<p>Xerox® Device Types for SAP R/3 Environment</p> <p>Information available at www.xeroxofficesapsolutions.com</p>	<p>Simplifies printing in SAP R/3 environments by providing users of SAP R/3 3.x, 4.x, 4.5x, 4.6x, SAP Enterprise 4.7x, ERP applications with enhanced WorkCentre printing functionality (PostScript and PCL):</p> <ul style="list-style-type: none"> • One- to two-sided printing • Finishing provides single or dual stapling • Tray pull location from any tray • Number of copies – provide the ability to print multiple copies • Paper Type and color – provide ability to select different paper types and paper colors, such as transparency, red, etc. • Print security via PIN ID capability • Network Accounting – Provides capability to add Network Accounting User IDs to SAP print jobs • Printer banner sheet – Provide the ability to enable/disable printer banner sheets • Barcode printing – Xerox standard PostScript device types available at www.xeroxofficesapsolutions.com supports Intelligent Barcode Printing with Xerox Barcode Pro PS. This Barcode Pro PS can be purchased at www.font.net. • Unicode Font Kit
<p>Xerox® SAP R/3 Intelligent Barcode Utility (optional)</p> <p>Information available at www.xeroxofficesapsolutions.com</p>	<p>Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer on the SAP R/3 4.1x, 4.5x, 4.6x and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox PostScript Device Types for SAP R/3 environment and Xerox Font Center Barcode Fonts. Utility enables automated checksum calculation, placement of start/stop characters, encoding of data string and data compression.</p>
<p>Xerox® Barcode Pro PS (optional)</p> <p>Information available at www.xeroxofficesapsolutions.com</p>	<p>Enables intelligent PostScript printing on Xerox multifunction systems by storing Xerox software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP R/3 client or mainframe) that supports PostScript printing. Automatically calculates the check digit, places start/stop and middle bar characters in the data string, compresses and encodes the data string, and rotates the barcode through 90 or 270 degrees.</p>
<p>CentreWare Internet Services – Integrated Web Pages Provided by the Device</p>	
<p>Device Status</p>	<p>Web server embedded in Network Controller:</p> <ul style="list-style-type: none"> • Tray status/contents • Consumables status • Alerts
<p>Job Submission</p>	<p>Print ready files: PS, PCL, TIFF, PDF, JPG, XPS Output feature selection (2-sided, output color, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)</p>
<p>Device Administration</p>	<p>Allows simple, remote installation setting of configuration options and management of the device</p>
<p>Browsers</p>	<p>Netscape 7.x, 9.x Internet Explorer 6.x, 7.x, 8.x Safari 3.0-3.2, 4.0.3 Mozilla Firefox 2.x, 3.5, 3.6.3 Opera 9.x, 10 Chrome 1.0, 4.1, 5.x</p>
<p>Support</p>	<p>Install print/scan drivers and online support available via web page</p>
<p>Languages Supported</p>	<p>International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish or Russian</p>

Smart eSolutions	
MeterAssistant®	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time. Device Direct or via Smart eSolutions Client for Windows or via CentreWare® Web.
SuppliesAssistant®	Automatically orders supplies for Xerox output devices based on actual usage, eliminating the need to manually manage supplies inventory. Device Direct or via Smart eSolutions Client for Windows or via CentreWare Web.
MaintenanceAssistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime. Device Direct
Online Support Assistant	Xerox® Online Support keeps you up and running by providing instant access to searchable online help right at the WorkCentre 7500 series multifunction printer's front panel. You get the same information our Product Support Specialists use when resolving printer problems, assisting with error codes, print quality, media jams, software installation, and more.
EFI Fiery Network Controller with System Software 9e (Optional)	
Processor	2.66 GHz, Intel Core 2 Duo E5300
Memory (ESS)	1 GB
System Disk	160 GB
Print Languages (PDL)	PostScript v 3019
Features	Command WorkStation capability via a PC or MAC (customer to provide) with Queue Management Job Preview Job Merge Change Job Properties Pantone Color Tables Expert Color Settings: Profile, Rendering and Simulation ColorWise Pro Tools – calibration support, color editor, profile manager FreeForm – Variable Data capabilities Booklet Maker 4.0 – booklet wizard to create booklets Print from USB flash drive Paper Catalog Secure Erase
Connectivity	10Base-T/100Base-TX/1000Base-T Ethernet
Optional	SeeQuence Suite (Impose & Compose) Mini-bundle (Spot On, Auto Trapping, Hot folders, Virtual Print) A la Carte Spot On, Auto Trapping, Hot folder/Virtual Printers)
Accounting	
Accounting – Xerox® Standard Accounting (Standard)	
Tracking	Copy, Print, Fax and Scan usage
Accounting	Up to 2,500 User accounts (User ID) Up to 500 General accounts (Client) Up to 500 Group accounts (Department)

Features	<p>Enable/disable via the Web User Interface or the device control panel in tools, Administrator can manage the feature remotely via the Web User Interface Data can be exported via a CSV file Supports entering Xerox® Standard Accounting ID into the print driver when submitting a print job</p>
Accounting Options – Network Accounting – Third Party Enablement	
	<ul style="list-style-type: none"> Enhanced network accounting with up to the minute data on how the WorkCentre system is being used Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax Various options are available through Xerox® Alliance Partner solutions. For details visit www.xerox.com Security enhancements with the addition of HTTPS protocol support WorkCentre requests account authentication from 3rd-party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to 3rd party Networking Account Interface with 3rd party accounting terminal for accounting user interface
Device Specifications	
Monthly Duty Cycle	
	<p>WorkCentre 7525: up to 75,000 pages/month WorkCentre 7530: up to 90,000 pages/month WorkCentre 7535: up to 110,000 pages/month WorkCentre 7545: up to 200,000 pages/month WorkCentre 7556: up to 300,000 pages/month</p>
Basic Configurations	
	<p>1 Tray Option 3 Tray Option High Capacity Tandem Tray Option</p>
Accessories	
Optional	<p>High Capacity Feeder Envelope Tray (Replaces Tray 1) Integrated Office Finisher (optional with 7525/7530/7535 only) Office Finisher LX Booklet Maker for Office Finisher LX Hole Punch for Office Finisher LX Professional Finisher Convenience Stapler (includes Work Surface) Common Access Card Enablement Kit Xerox® Secure Access Unified ID System® (with USB Card Reader) EFI® Fiery Network Controller Foreign Device Interface Xerox® Copier Assistant® Walk up Fax (One- or Two-line options, includes LAN Fax) Xerox® Scan to PC Desktop® ScanFlowStore® Xerox® Unicode International Print Kit</p>
Foreign Device Interface (FDI) (Optional)	<p>Interface to third party access control devices, coin machines, card readers Support a variety of vending stations available through the Xerox® Custom Application Service</p>
Accessibility Option	<p>Xerox® Copier Assistant® (XCA) Software provides a PC-based alternative to the user interface touch screen. Used in conjunction with a customer-supplied PC attached via the USB port, this software supports text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features. Section 508 compliant. For more information, visit www.xerox.com.</p>
Electrical Requirements	
North America	<p>Voltage : 110 –127 VAC +/- 10 % Frequency: 50/60 Hz +/- 3 % , 15 A Power Consumption: 1.108 KVA maximum printing continuously (120V)</p>

Europe	Voltage : 220-240 VAC +/- 10 % Frequency: 50/60 Hz +/- 3 %, 10 A Power Consumption: 1.203 KVA maximum printing continuously (240V), 1.760 KVA maximum printing continuously (220)			
Power Consumption (Base IOT)				
Running (Average)	984 watts/hour			
Standby Mode	130 watts/hour			
Low Power Mode	82 watts/hour			
Auto Off / Sleep mode	9.1 watts/hour (Default time to Sleep mode = 2 minutes)			
Warm-up	2 minutes, 59 seconds			
Low Power Recovery	< 9 seconds			
Operating Environment				
Required Temperature Range	50° to 82° F (10° to 28° C)			
Required Relative Humidity	15 % to 85 %			
Sound Power Levels	Operating 7.5 B(A), Standby: 3.6 B(A)			
Sound Pressure Levels	Operating: 58 dB(A), Standby: 18 dB(A)			
Dimensions and Weight	Width	Depth	Height	Weight
Base Configuration	41.9 in. / 1,064 mm	27 in. / 685 mm	44.4 in. / 1,127 mm	308 lbs. / 140 kg
With Integrated Office Finisher	44.4 in. / 1,129 mm	27 in. / 685 mm	44.4 in. / 1,127 mm	334 lbs. / 152 kg
With Office Finisher LX (with Booklet Maker)	65.6 in. / 1,666 mm	27.4 in. / 695 mm	44.4 in. / 1,127 mm	390 lbs. / 177 kg
With Professional Finisher	75.7 in. / 1,922 mm	27 in. / 685 mm	44.4 in. / 1,127 mm	502 lbs. / 228 kg
With Professional Finisher and High Capacity Feeder	75.7 in. / 1,922 mm	27 in. / 685 mm	44.4 in. / 1,127 mm	564 lbs. / 256 kg
Certifications				
	FCC Class A Compliant (US), ICES Class A Compliant (Canada) TUV Listed (UL 60950-1, Second Edition) CB Certified (IEC 60950-1, Second Edition) 2006/95/EC (Europe) 2005/32/EC (Europe) 2004/108/EC (Europe) 199/5/EC (Europe) ENERGY STAR® GOST NOM Blue Angel Environmental Choice CE Certification Common Criteria (IEEE 2600.2 standard)			

Xerox® WorkCentre® 7525/7530/7535/7545/7556

Supplies	Description	Yield	Order Number
Toner Cartridges (Metered)	Black	26,000 ³	006R01509
	Cyan	15,000 ³	006R01512
	Magenta	15,000 ³	006R01511
	Yellow	15,000 ³	006R01510
Toner Cartridges (Sold)	Black	26,000 ³	006R01513
	Cyan	15,000 ³	006R01516
	Magenta	15,000 ³	006R01515
	Yellow	15,000 ³	006R01514
Transfer Belt Cleaner	1 Assembly	160,000 ³	001R00613
Second Bias Transfer Roll	1 Assembly	200,000 ³	008R13064
Staple Cartridge	for Integrated Office Finisher, Office Finisher LX, Professional Finisher and Convenience Stapler (1 cartridge per carton)	5,000 each cartridge	008R12964
Staple Cartridge	for Office Finisher LX Booklet Maker (8 cartridge per carton)	2,000 each cartridge	008R12897
Staple Cartridge	for Professional Finisher Booklet Maker (1 cartridge per carton)	5,000 each cartridge	008R12925
Staple Refills	for Integrated Office Finisher, Office Finisher LX, Professional Finisher and Convenience Stapler (3 refills per carton)	5,000 each refill	008R12941
Smart Kits®	Description	Yield	Order Number
Drum Cartridge	1 Cartridge	125,000 ³	013R00662
Waste Toner Container	1 Cartridge	43,000 ³	008R13061

³ Approximate pages. Declared Yield based on 5 page job size, 30% color and 70% Black and white ratio, using letter-/A4-size media. Yield will vary based on media size, image area coverage, media orientation and usage patterns.

